



POWER ANNUNCIATOR

AYK-018

INTRODUCTION

The digital annunciator unit is used in a variety of applications requiring supervision of alarm and signaling contacts in power plants, substations and industrial process installations. The alarm unit is also approved for use in off-shore installations and marine applications. Further, the annunciator unit can be used in any application where on/off signals are to be supervised.

The annunciator unit provides immediate fault recognition, fault identification and visual and audioable alarm in an abnormal process situation. The annunciator unit also provides a means for subsequent fault analysis, which means that corrective measures can be carried out without delay and full control of the processes can be maintained.

FEATURES

- ▶ Microcontroller based logic
- ▶ 8 contact inputs
- ▶ Super bright LCD with Backlight LEDs
- ▶ Low power, Long life illumination
- ▶ Intelligent fault processing
- ▶ Analogue input are possible
- ▶ 16 in 1 pack, (NEW FEATURE)



Technical Data

Power supply:	Universal SMPS 110V DC 230 AC
Number of points:	4, 6, 8, & 12 Available
Output:	1 N/O for audioable hooter & Display
Output Rating:	6 amps at 230 V AC (resistive)
Window Size:	40 x 100 mm
Status indication:	LCD with backlight LEDs
Push buttons:	TEST, ACK, and RESET push buttons provided. (Fast, Ack and Reset)
Environmental Temperature:	0 to 75 °C
Humidity:	Up to 95% RH (non condensing)
Dimensions:	135mm x 90mm x 150mm (WxHxD)
Weight:	380Grams
Protection Class	Ip54


Ayk (Pvt.) Ltd.
 E-mail: info@ayk.com.pk



ISO Certified
9001 - 2001
CE

HEAD OFFICE:

Al-Sharif Market Main Model Town Road,
Near LG office, Gujranwala-Pakistan.
Ph # +92-055-3255800, 3843269 Fax # 055-3736674
UAN: 055-111-ayk-ayk www.ayk.com.pk

BRANCH OFFICES:

After Sale Service offices
Lahore. 042 5877212
Islamabad. 051 2830564
Karachi. 0321 6456491